



1 2 3 4

35 kV AERIAL CABLE
397.5 KCM AAC (201mm²) 75° C BLACK

CONSTRUCTION:

1	397.5 KCM (201mm ²)	19 Strand Compact Round AAC All-Aluminum 1350-H19 Conductor
2	0.015" (0.381 mm)	Black Semiconducting Thermoplastic Polyethylene
3	0.175" (4.445 mm)	Natural Low Density Thermoplastic Polyethylene (HMWPE)
4	0.125" (3.175 mm)	Black Track and UV Resistant High Density Thermoplastic Polyethylene

DIAMETERS:

1	0.659" (16.739 mm)	Nom.
2	0.689" (17.501 mm)	Nom.
3	1.039" (26.391 mm)	Nom.
4	1.289" (+.020"/-.010")	(32.741 mm + 0.5 mm / -0.25 mm)

CABLE DATA:

1	Cable Weight:	776 lb/ 1000 ft	(1154 kg/km)
2	Conductor Weight:	373 lb/ 1000 ft	(556 kg/km)
3	Conductor Operating Temperature:	75° C	
4	D.C. Resistance @ 20°C:	0.044 ohms/1000 ft.	(0.1444 ohms/km)
5	Conductor Breaking Strength:	7110 lbs (3225 kg)	(32 kN)
6	Normal Ampacity:	494 Amps	*
7	Emergency Ampacity:	623 Amps	**

*75°C Conductor, 25°C Ambient, 2 ft/sec. (0.6096 m/s) Wind, Sun

**100°C Conductor, 25°C Ambient, 2 ft/sec. Wind, Sun