



1 2 3 4

15 kV AERIAL CABLE
556.5 KCM AAC (282mm²) 75° C BLACK

CONSTRUCTION:

1	556.5 KCM (282mm ²)	19 Strand Compact Round AAC All-Aluminum 1350-H19 Conductor
2	0.020" (0.508 mm)	Black Semiconducting Thermoplastic Polyethylene
3	0.075" (1.905 mm)	Natural Low Density Thermoplastic Polyethylene (HMWPE)
4	0.075" (1.905 mm)	Black Track and UV Resistant High Density Thermoplastic Polyethylene

DIAMETERS:

1	0.780" (19.812 mm)	Nom.
2	0.820" (20.828 mm)	Nom.
3	0.970" (24.638 mm)	Nom.
4	1.120" (+.020"/-.010")	(28.448 mm + 0.5 mm / -0.25 mm)

CABLE DATA:

1	Cable Weight:	741 lb/ 1000 ft	(1102 kg/km)
2	Conductor Weight:	522 lb/ 1000 ft	(777 kg/km)
3	Conductor Operating Temperature:	75° C	
4	D.C. Resistance @ 20°C:	0.031 ohms/1000 ft.	(0.1017 ohms/km)
5	Conductor Breaking Strength:	9750 lbs (4423 kg)	(44 kN)
6	Normal Ampacity:	641 Amps	*
7	Emergency Ampacity:	810 Amps	**

*75°C Conductor, 25°C Ambient, 2 ft/sec. (0.6096 m/s) Wind, Sun

**100°C Conductor, 25°C Ambient, 2 ft/sec. Wind, Sun