



25 kV AERIAL CABLE
795 KCM AAC (403mm²) 75° C BLACK

CONSTRUCTION:

1	795 KCM (403mm ²) 19 Strand Compact Round AAC All-Aluminum 1350-H19 Conductor
2	0.020" (0.508 mm) Black Semiconducting Thermoplastic Polyethylene
3	0.125" (3.175 mm) Natural Low Density Thermoplastic Polyethylene (HMWPE)
4	0.125" (3.175 mm) Black Track and UV Resistant High Density Thermoplastic Polyethylene

DIAMETERS:

1	0.932" (23.673 mm)	Nom.
2	0.972" (24.689 mm)	Nom.
3	1.222" (31.039 mm)	Nom.
4	1.472" (+.020"/-.010")	(37.389 mm + 0.5 mm / -0.25 mm)

CABLE DATA:

1	Cable Weight:	1176 lb/ 1000 ft	(1750 kg/km)
2	Conductor Weight:	746 lb/ 1000 ft	(1111 kg/km)
3	Conductor Operating Temperature:	75° C	
4	D.C. Resistance @ 20°C:	0.022 ohms/1000 ft.	(0.0722 ohms/km)
5	Conductor Breaking Strength:	13700 lbs (6214 kg)	(61 kN)
6	Normal Ampacity:	765 Amps	*
7	Emergency Ampacity:	973 Amps	**

*75°C Conductor, 25°C Ambient, 2 ft/sec. (0.6096 m/s) Wind, Sun

**100°C Conductor, 25°C Ambient, 2 ft/sec. Wind, Sun