

QTY DESIGN PARAMETERS 1 HENDRIX AERIAL CABLE, (SIZE AND VOLTAGE AS REQ.)
2 MESSENGER, (SIZE AND TYPE AS REQ.) AS REQ 15kV 3 INSULATOR, PIN TYPE, HENDRIX HPI-15VTP 6 DOUBLE CROSS-ARM CONSTRUCTION INSULATOR PIN, LONG SHANK HENDRIX LSP-1 6 5 PRESHAPED CONDUCTOR GRIP, COATED 6 PRESHAPED MESSENGER GRIP 6 7 INSULATOR, POLYMER DEAD-END HENDRIX DEINS15 **DEAD-END TRANSITION:** LIGHTNING ARRESTER WITH MOUNTING BRACKET 3 THIMBLE CLEVIS, CATALOG NO. TC 3 SPACER CABLE TO BARE WIRE DOUBLE ARMING BOLT, 5/8" X REQ. LENGTH DRAWING NO. REV AS REC GROUND WIRE, SOFT DRAWN COPPER, SOLID, #6 AWG MIN. 12 AC1248-01 5 SPACER CABLE SYSTEMS GROUND WIRE STAPLE CONNECTORS, (SIZE AND TYPE AS REQ.) EYE BOLT, 3/4" X REQ. LENGTH 3/18/16 16 HEAVY DUTY THIMBLE CLEVIS, HENDRIX HDTC 1 UNIVERSAL GROOVE CLAMP, SIZE AND TYPE AS REQUIRED DEAD-END CLAMP FOR BARE WIRE, SIZE AND TYPE AS REQUIRED 19 HENDRIX LINEDUC, 8FT LONG 1 **AERIAL CABLE SYSTEMS** 20 SHACKLE CLEVIS, HENDRIX TYPE SC 53 OLD WILTON RD. • MILFORD, NH 03055 • 603-673-2040