

Hendrix Trunnion Insulators are molded from a proprietary blend of track-resistant, high-density polyethylene and are ideal for use with bare wire conductors. They are more durable and reliable than traditional porcelain insulators, as well as lighter, safer, and easier to handle.

HPI Trunnion Insulators meet the electrical and mechanical requirements of ANSI C29.7 and C29.18. They are designed with a 3/4-10 inch center hole thread and are a direct replacement for porcelain or composite insulators.

Benefits

- Short lead time
- Easy handling: lighter than porcelain
- · HDPE prevents chips, cracks, and breaks
- Resistant to impact damage, breakage, and vandalism
- Made in the USA
- Guaranteed for life







Part Number	Description	Voltage	ANSI Class	Stud Size
HPI-TLP-15V	Trunnion Style Line Post, Vertical Position	25kV	57-11/51-12	3/4" - UNC 10
HPI-TLP-15H	Trunnion Style Line Post, Horizontal Position	25kV	57-21/51-22	3/4" - UNC 10
HPI-TLP-17V	Trunnion Style Line Post, Vertical Position	35kV	57-12/51-13	3/4" - UNC 10
HPI-TLP-17H	Trunnion Style Line Post, Horizontal Position	35kV	57-22/51-23	3/4" - UNC 10
HPI-TLP-20V	Trunnion Style Line Post, Vertical Position	46kV	57-13/51-14	3/4" - UNC 10
HPI-TLP-20H	Trunnion Style Line Post, Horizontal Position	46kV	57-23/51-24	3/4" - UNC 10
HPI-TLP-25V	Trunnion Style Line Post, Vertical Position	69kV	57-14/51-15	3/4" - UNC 10
HPI-TLP-25H	Trunnion Style Line Post, Horizontal Position	69kV	57-24/51-25	3/4" - UNC 10



