



## HPI-SP-14

Technical Reference Number: 208P

Hendrix Station Line Post Insulators are molded from a proprietary blend of gray, track and UV resistant, high-density polyethylene. They are more durable and reliable than traditional porcelain insulators.

The HPI-SP-14 has 4-hole pattern steel plates, tapped with ½-13 unified form special threads with 3-inch bolt circle. It meets the electrical and mechanical requirements of ANSI C29.19.

- Lighter than porcelain
- Designed for use in vertical and horizontal configurations
- Resistant to impact damage, breakage and vandalism
- Molded in USA

## PRODUCT DATA

Characteristic	ANSI C29.9	ANSI C29.19	HPI-SP-14
<b>DIMENSIONS</b>			
Leakage distance (in.)	24	24	28.9
Dry-arc distance (in.)	N/A	N/A	12.5
4 hole pattern – thread size (in.)	½-13	½-13	½-13
Bolt Circle diameter (in.)	3	3	3
<b>MECHANICAL VALUES</b>			
Cantilever load (lbs.)	2,000	2,000	>2,000
Tensile strength (lbs.)	10,000	10,000	>10,000
Compressive strength (lbs.)	10,000	10,000	>10,000
Torsional strength (in-lbs.)	8,000	6,000	>8,000
Deflection @ 50% RCL (in.)			0.25
<b>ELECTRICAL VALUES</b>			
Typical application (kV)	25	25	25
Flashover, 60 Hz Dry (kV)	N/A	N/A	152
Withstand 10 sec hold, 60 Hz Wet (kV)	60	60	60
Critical Impulse Flashover – Pos. (kV)	170	165	256
Impulse Withstand – Positive (kV)	150	150	238
Impulse Flashover – Negative (kV)	N/A	N/A	N/A
Max RIV tested at 30kV (µV)	100	100	<100
<b>OTHER</b>			
Part Weight (lbs.)	-	-	11.9

